

Fibreglass tape 130 °C
for heat-proof electrical and mechanical insulation

Self-adhesive fibreglass tape coated with heat-hardening silicone adhesive, temperature-resistant up to 130 °C.



Product description

Article name	Premio 1130
Article number	223583

Characteristics
Stable core
Inscribable
Extreme tear resistance
Superior thermal stability

Applications
Insulation of highly exothermic electrical components
As a cable protection during welding and soldering
As a protection wrapping against radiant heat

Technical data

Article name	Premio 1130
Article number	223583
Materials	Fibreglass reinforcement
Length L	33 m
Width B	19 mm
Thickness	0.17 mm
Colours	white
Adhesive strength	3.8 N/cm
Elongation at break	8 %
Heat resistance max	130 °C
Dielectric strength	12.7 kV/mm
Insulation resistance	1500 MΩ

Logistics data

Article name	Premio 1130
Article number	223583
Delivery scope	Fibreglass tape
Country of origin	Germany
Customs tariff number	39191012
EAN/GTIN	4010311124247

Packaging data

Alternative unit of measure	Bag1	Carton
Base quantity	1	50
Base unit of measure	Piece	Piece
Lenght (mm)	117	350
Width (mm)	117	350
Height (mm)	20	240
Net weight (kg)	0.162	8.1
Gross weight (kg)	0.162	8.4