

Fibreglass tape 180 °C
for heat-proof electrical and mechanical insulation

Self-adhesive fibreglass tape coated with heat-hardening silicone adhesive, temperature-resistant up to 180 °C.



Product description

Article name	Premio 1180
Article number	223580

Characteristics
Particularly high temperature resistance
Excellent mechanical strength
Very good form adaptability
Good solvent and paint resistance
Extreme tear resistance
Inscribable
Stable core

Applications
Insulation of highly exothermic electrical components
As a cable protection during welding and soldering
As a protection wrapping against radiant heat

Technical data

Article name	Premio 1180
Article number	223580
Materials	Fibreglass reinforcement
Length L	33 m
Width B	25 mm
Thickness	0.17 mm
Colours	white
Adhesive strength	3.8 N/cm
Elongation at break	8 %
Tensile strength at break	300 N/cm
Heat resistance max	180 °C
Breakdown voltage	3 kV
Insulation resistance	1500 MΩ

Logistics data

Article name	Premio 1180
Article number	223580
Delivery scope	Fibreglass tape
Country of origin	Germany
Customs tariff number	39191012
EAN/GTIN	4010311124216

Packaging data

Alternative unit of measure	Bag1	Carton
Base quantity	1	50
Base unit of measure	Piece	Piece
Lenght (mm)	117	350
Width (mm)	117	350
Height (mm)	25	235
Net weight (kg)	0.218	10.9
Gross weight (kg)	0.218	11.2