

## Pressure spring

for permanently elastic contact

Used on lead and aluminum cable sheaths, cable screening tapes or wires and steel or aluminum armor wires.



### Product description

Article name	RF 4
Article number	456343
Notes	Pressure springs are no currentcarrying parts.

#### Characteristics

Corrosion-resistant

Fatigue-proof

Guarantees consistent radial contact stress

#### Applications

For cast resin, heat shrinkable and slip-on cable accessories

Enables solder-free electrical connection of metal cable components (screen, armouring, metal sheath) and earthing elements (copper grounding wire, cooper mesh joint etc.)

## Technical data

Article name	RF 4
Article number	456343
Materials	Special stainless steel
Selection Note	10 Pressure springs
Width B	16 mm
Diameter cable min	33 mm
Diameter cable max	49 mm
Outer diameter	29 mm

## Logistics data

Article name	RF 4
Article number	456343
Delivery scope	10 Pressure springs
Country of origin	Great Britain
Customs tariff number	73209010
EAN/GTIN	4010311199665

## Packaging data

Alternative unit of measure	Bag
Base quantity	10
Base unit of measure	Piece
Length (mm)	133
Width (mm)	105
Height (mm)	32
Net weight (kg)	0.22
Gross weight (kg)	0.223