

## Heat shrinkable tube in dispenser box

thin wall shrink ratio 2 : 1 without adhesive

The heat shrinkable tubes type SB 2:1 are thin-walled, without thermoplastic adhesive with a shrinkage ratio of 2:1. Typical applications are the protection of cables against chemical influences as well as good mechanical protection.



### Product description

|                |   |
|----------------|---|
| Article name   | SB 4.8-2.4  |
| Article number | 127052  |
| Notes          | A standard spool may include sections which have been tied together.<br>See „SR1F“ heat shrinkable tube for further information on product properties |

#### Characteristics

|   |
|---|
| Back-winding mechanism facilitates rolling up of tube             |
| User friendly, notch prevents tube from rolling back into the box |
| Déroulement facilité  |
| Self-extinguishing (except transparent)                           |

#### Applications

|                       |
|-----------------------|
| Bundling              |
| Marking               |
| Corrosion protection  |
| Mechanical protection |

## Technical data

|   |                          |
|---|--------------------------|
| Article name                            | SB 4.8-2.4               |
| Article number                          | 127052                   |
| Test standards                          | UL E172094               |
|   | MIL-I-23053/5 Class 1    |
| Materials                               | Cross-linked polyolefin  |
|   | Free of lead and cadmium |
| Length L                                | 10 m                     |
| Colours                                 | blue                     |
| Inner diameter before shrinking (inch)  | 3/16"                    |
| Inner diameter before shrinking (mm)    | 4.8 mm                   |
| Inner diameter after shrinking (mm)     | 2.4 mm                   |
| Recovered wall thickness                | 0.51 mm                  |
| Burning behaviour                       | self-extinguishing       |
| Burning behaviour (associated standard) | UL 224                   |
| Corrosion                               | none                     |
| Corrosion (associated standard)         | ASTM D 2671              |

## Logistics data

|                        |   |
|------------------------|---|
| Article name           | SB 4.8-2.4                                      |
| Article number         | 127052  |
| Delivery scope         | Thin wall heat shrinkable tube in dispenser box |
| Shelf life description | Unlimited shelf life                            |
| Country of origin      | Poland  |
| Customs tariff number  | 39173200  |
| EAN/GTIN               | 4010311035833                                   |

## Packaging data

| Alternative unit of measure | Case  | Carton |
|-----------------------------|-------|--------|
| Base quantity               | 1     | 36     |
| Base unit of measure        | Piece | Piece  |
| Length (mm)                 | 168   | 410    |
| Width (mm)                  | 168   | 410    |
| Height (mm)                 | 55    | 415    |
| Net weight (kg)             | 0.137 | 4.932  |
| Gross weight (kg)           | 0.137 | 5.232  |