

## Heat shrinkable tube in dispenser box

thin wall shrink ratio 3 : 1 without adhesive

The heat shrinkable tubes type SB 3:1 are thin-walled, without thermoplastic adhesive with a shrinkage ratio of 3:1. Typical applications are the protection of cables against chemical influences as well as good mechanical protection.



### Product description

Article name	SB 18-6
Article number	127132
Notes	A standard spool may include sections which have been tied together. See „SR1F3“ heat shrinkable tube for further information on product properties

#### Characteristics

- Back-winding mechanism facilitates rolling up of tube
- User friendly, notch prevents tube from rolling back into the box
- Déroulement facilité
- Self-extinguishing (except transparent)

#### Applications

- Bundling
- Marking
- Corrosion protection
- Mechanical protection

## Technical data

Article name	SB 18-6
Article number	127132
Test standards	UL E172094
	MIL-I-23053/5 Class 1
Materials	Cross-linked polyolefin
	Free of lead and cadmium
Length L	7 m
Colours	black
Inner diameter before shrinking (mm)	18 mm
Inner diameter after shrinking (mm)	6 mm
Recovered wall thickness	0.75 mm
Burning behaviour	self-extinguishing
Burning behaviour (associated standard)	UL 224
Corrosion	none
Corrosion (associated standard)	ASTM D 2671

## Logistics data

Article name	SB 18-6
Article number	127132
Delivery scope	Thin wall heat shrinkable tube in dispenser box
Shelf life description	Unlimited shelf life
Country of origin	Poland
Customs tariff number	39173200
EAN/GTIN	4010311037035

## Packaging data

Alternative unit of measure	Case	Carton
Base quantity	1	36
Base unit of measure	Piece	Piece
Length (mm)	169	410
Width (mm)	165	410
Height (mm)	57	415
Net weight (kg)	0.261	9.396
Gross weight (kg)	0.261	9.696