

Heat shrinkable spreader cap

for 2- 3- 4- 5-core cables with adhesive

Sealing spreader caps for plastic-, rubber- and paper-insulated cables.




Product description

Article name	SEH3 125-59
Article number	125371
Notes	Recovered dimension after shrinking 3-fingers spreader cap

Characteristics
With hot melt adhesive
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
Superior electrical properties
Pressure-tight
Superior mechanical properties
100 % waterproof

Applications
Indoor
Outdoor

Technical data



Article name	SEH3 125-59
Article number	125371
Test standards	IEC 60684-2
Materials	Cross-linked polyolefin Free of lead and cadmium
Article notes	3-fingers spreader cap
Selection Note	3-fingers spreader cap
Length L1	208 mm
Length L1*	268 mm
Length L2	51 mm
Colours	black
Inner diameter D1 before shrinking	125
Inner diameter D1 after shrinking	59
Inner diameter D2 before shrinking	67
Inner diameter D2 after shrinking	27
Recovered wall thickness	4.4 mm
Nominal cross section min	240 mm ²
Nominal cross section max	500 mm ²
Elongation at break	300 %
Elongation at break (associated standard)	IEC 62677-2
Tensile strength at break	10 MPa
Tensile strength at break (associated standard)	IEC 62677-2
Operating temperature range min	-40 °C
Operating temperature range max	100 °C
Operating temperature range (associated standard)	IEC 62677-2
Shrinkage temperature	> 110 °C
Burning behaviour	not self-extinguishing
Burning behaviour (associated standard)	IEC 60684-2
Flexibility at low temperatures	-40 °C
Flexibility at low temperatures (associated standard)	IEC 62677-2

Thermal ageing (168 h at 150 °C): Elongation at break	200 %
Thermal ageing (168 h bei 150 °C): Tensile strength at break	8 MPa
Thermal ageing (168 h bei 150 °C) (associated standard)	IEC 62677-2
Specific volume resistivity	10 ¹² Ω cm
Specific volume resistivity (associated standard)	EN 62677-2
Dielectric strength	10 kV/mm
Dielectric strength (associated standard)	IEC 60243-1
Corrosion	none
Corrosion (associated standard)	EN 62677-2
Resistance to fungus and decay	Rate 1
Resistance to fungus and decay (associated standard)	IEC 62677-2

Logistics data

Article name	SEH3 125-59
Article number	125371
Delivery scope	Heat shrinkable spreader cap
Shelf life description	Unlimited shelf life
Country of origin	India
Customs tariff number	39174000
EAN/GTIN	4010311115214

Packaging data

Alternative unit of measure	Bag	Carton
Base quantity	5	30
Base unit of measure	Piece	Piece
Length (mm)	900	810
Width (mm)	190	610
Height (mm)	190	525
Net weight (kg)	1.32	7.92
Gross weight (kg)	1.325	8.22