

Heat shrinkable spreader cap
for 2- 3- 4- 5-core cables with adhesive

Sealing spreader caps for plastic-, rubber- and paper-insulated cables.




Product description

Article name	SEH4 47-23
Article number	166973
Notes	Recovered dimension after shrinking 4-fingers spreader cap

Characteristics
With hot melt adhesive
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
Superior electrical properties
Pressure-tight
Superior mechanical properties
100 % waterproof

Applications
Indoor
Outdoor

Technical data



Article name	SEH4 47-23
Article number	166973
Test standards	IEC 60684-2
Materials	Cross-linked polyolefin Free of lead and cadmium
Article notes	4-fingers spreader cap
Selection Note	4-fingers spreader cap
Length L1	134 mm
Length L1*	169 mm
Length L2	36 mm
Colours	black
Inner diameter D1 before shrinking	47
Inner diameter D1 after shrinking	23
Inner diameter D2 before shrinking	20
Inner diameter D2 after shrinking	7
Recovered wall thickness	4.1 mm
Nominal cross section min	35 mm ²
Nominal cross section max	95 mm ²
Elongation at break	300 %
Elongation at break (associated standard)	IEC 62677-2
Tensile strength at break	10 MPa
Tensile strength at break (associated standard)	IEC 62677-2
Operating temperature range min	-40 °C
Operating temperature range max	100 °C
Operating temperature range (associated standard)	IEC 62677-2
Shrinkage temperature	> 110 °C
Burning behaviour	not self-extinguishing
Burning behaviour (associated standard)	IEC 60684-2
Flexibility at low temperatures	-40 °C
Flexibility at low temperatures (associated standard)	IEC 62677-2

Thermal ageing (168 h at 150 °C): Elongation at break	200 %
Thermal ageing (168 h bei 150 °C): Tensile strength at break	8 MPa
Thermal ageing (168 h bei 150 °C) (associated standard)	IEC 62677-2
Specific volume resistivity	10 ¹² Ω cm
Specific volume resistivity (associated standard)	EN 62677-2
Dielectric strength	10 kV/mm
Dielectric strength (associated standard)	IEC 60243-1
Corrosion	none
Corrosion (associated standard)	EN 62677-2
Resistance to fungus and decay	Rate 1
Resistance to fungus and decay (associated standard)	IEC 62677-2

Logistics data

Article name	SEH4 47-23
Article number	166973
Delivery scope	Heat shrinkable spreader cap
Shelf life description	Unlimited shelf life
Country of origin	India
Customs tariff number	39174000
EAN/GTIN	4010311041209

Packaging data

Alternative unit of measure	Bag	Carton
Base quantity	5	350
Base unit of measure	Piece	Piece
Length (mm)	310	830
Width (mm)	145	430
Height (mm)	65	570
Net weight (kg)	0.27	18.9
Gross weight (kg)	0.275	19.2