

Heat shrinkable cable termination
for unarmoured polymeric cables

Universally suitable to terminate polymeric cables and electrical equipment. Suitable for cables insulated with PE, VPE, PVC und cable sheaths insulated with PVC or PE suitable for compression lugs on aluminium and copper conductors.



Product description

Article name	SFEH4 4-16
Article number	145435
Optional accessory	Compression cable lugs (see Connecting technology)

Characteristics
Compact dimensions
Wide conductor and cross-section range
Resistant to chemical agents
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
High electrical insulating values
High mechanical strength

Applications
Indoor

Technical data

Article name	SFEH4 4-16
Article number	145435
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Nominal cross section Polymeric cable unarmoured per conductor 4x min	4 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 4x max	16 mm ²

Logistics data

Article name	SFEH4 4-16
Article number	145435
Delivery scope	Spreader cap
	Sealing tubes
	Cleaning tissue
	Emery cloth
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39174000
EAN/GTIN	4010311004600

Packaging data

Alternative unit of measure	Bag1	Pal. OW
Base quantity	1	1000
Base unit of measure	Piece	Piece
Length (mm)	209	1200
Width (mm)	119	800
Height (mm)	47	1130
Net weight (kg)	0.057	57
Gross weight (kg)	0.057	75.2