

Heat shrinkable wall duct
for cables

Universally suitable for insertion of all types of cables
and conduits through building walls.



Product description

Article name	SHE 54-26
Article number	145611
Notes	For very thick walls two wall ducts may be joined together.
Optional accessory	Centring aid KZ (see Accessories)
	Putty/sealing compound LG, Universal sealing compound DUCT SEAL (see Accessories)

Characteristics

Wide conductor and cross-section range
Extension possible
Sealant-coated on the inside
Resistant to alkaline earth elements
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
100 % waterproof
Longitudinally watertight up to 1.0 bar
High mechanical strength

Applications

Mechanical protection for cables and conduits routed through walls
--

Technical data

Article name	SHE 54-26
Article number	145611
Length L	800 mm
Inner diameter before shrinking (mm)	65 mm
Inner diameter after shrinking (mm)	25 mm
max. wall thickness mm	500 mm
Wall breakthrough	90 mm
Diameter cable min	26 mm
Diameter cable max	54 mm

Logistics data

Article name	SHE 54-26
Article number	145611
Delivery scope	Wall duct
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Malaysia
Customs tariff number	39173900
EAN/GTIN	4010311005317

Packaging data

Packaging type	Bag1	Carton	Pal. OW
Content quantity	1	60	180
Unit of measure	Piece	Piece	Piece
Lenght (mm)	800	800	1200
Width (mm)	85	395	800
Height (mm)	82	840	1000
Net weight (kg)	0.65	39	117
Gross weight (kg)	0.65	39.3	135.2