

Heat shrinkable wall duct  
for cables

Universally suitable for insertion of all types of cables  
and conduits through building walls.



Product description

Article name	SHE 95-54
Article number	145614
Notes	For very thick walls two wall ducts may be joined together.
Optional accessory	Centring aid KZ (see Accessories)
	Putty/sealing compound LG, Universal sealing compound DUCT SEAL (see Accessories)

Characteristics

Wide conductor and cross-section range
Extension possible
Sealant-coated on the inside
Resistant to alkaline earth elements
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
100 % waterproof
Longitudinally watertight up to 1.0 bar
High mechanical strength

Applications

Mechanical protection for cables and conduits routed through walls
--

## Technical data

Article name	SHE 95-54
Article number	145614
Length L	800 mm
Inner diameter before shrinking (mm)	115 mm
Inner diameter after shrinking (mm)	35 mm
max. wall thickness mm	500 mm
Wall breakthrough	140 mm
Diameter cable min	54 mm
Diameter cable max	95 mm

Logistics data

Article name	SHE 95-54
Article number	145614
Delivery scope	House connection point
	Installation instruction
Shelf life description	Unlimited shelf life
Country of origin	Malaysia
Customs tariff number	39173900
EAN/GTIN	4010311005324

Packaging data

Packaging type	Bag1	Carton	Pal. OW
Content quantity	1	20	60
Unit of measure	Piece	Piece	Piece
Lenght (mm)	825	795	1200
Width (mm)	130	395	800
Height (mm)	130	840	1000
Net weight (kg)	1.332	26.64	79.92
Gross weight (kg)	1.332	26.94	98.12