

Heat shrinkable wall duct

for cables

Universally suitable for insertion of all types of cables and conduits through building walls.



Product description

Article name	SHE 95-54
Article number	145614
Notes	For very thick walls two wall ducts may be joined together.
Optional accessory	Centring aid KZ (see Accessories) Putty/sealing compound LG, Universal sealing compound DUCT SEAL (see Accessories)

Characteristics

Wide conductor and cross-section range

Extension possible

Sealant-coated on the inside

Resistant to alkaline earth elements

Stabilized against UV rays

Free from paint-wetting inhibiting substances

Halogen-free

100 % waterproof

Longitudinally watertight up to 1.0 bar

High mechanical strength

Applications

Mechanical protection for cables and conduits routed through walls

Technical data

Article name	SHE 95-54
Article number	145614
Length L	800 mm
Inner diameter before shrinking (mm)	115 mm
Inner diameter after shrinking (mm)	35 mm
Wall thickness max	500 mm
Wall breakthrough	140 mm
Diameter cable min	54 mm
Diameter cable max	95 mm

Logistics data

Article name	SHE 95-54
Article number	145614
Delivery scope	Wall duct
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Malaysia
Customs tariff number	39173900
EAN/GTIN	4010311005324

Packaging data

Alternative unit of measure	Bag1	Carton	Pal. OW
Base quantity	1	20	60
Base unit of measure	Piece	Piece	Piece
Length (mm)	825	795	1200
Width (mm)	130	395	800
Height (mm)	130	840	1000
Net weight (kg)	1.332	26.64	79.92
Gross weight (kg)	1.332	26.94	98.12