

Insulating and lubricating oil spray

water repellent prevents from flashover

High-quality, viscous insulating oil with a dielectric strength of 12 kV per millimetre. Does not dry out, water-repellent, suitable as a moisture buffer. Temperature resistant from -50° C to +200° C; does not attack construction materials, non-toxic.



Product description

Article name	SILICON Spray
Article number	124032

Characteristics	Applications
Does not damage rubber, plastics, textiles or varnished surfaces	Elimination or prevention of current leakage, corona discharges, soft short circuits
	Wire feed lubricant
	Insulating
	Protection of high-voltage equipment and tube sockets against flying sparks
	Short-circuit protection
	Can be used as a separating agent for plastics
	Prevents treated components from sticking together

Technical data

Article name	SILICON Spray
Article number	124032
Content	0.4 l
Colours	transparent color
Viscosity (20 °C)	1000 cP
Flash point	-97 °C
Density	0.55 g/cm³
Heat resistance min	-50 °C
Heat resistance max	200 °C
Dielectric strength	12 kV/mm

Logistics data

Article name	SILICON Spray
Article number	124032
Delivery scope	Insulating and lubricating oil spray
Shelf life	24 Month
Storage temperatur max	25 °C
Storage temperatur min	20 °C
Country of origin	France
Customs tariff number	34039900
EAN/GTIN	4010311057262

Packaging data

Alternative unit of measure	Tin	Carton	Pal. EU
Base quantity	1	12	900
Base unit of measure	Piece	Piece	Piece
Lenght (mm)	67	270	1200
Width (mm)	67	202	800
Height (mm)	200	203	1400
Net weight (kg)	0.355	4.26	319.5
Gross weight (kg)	0.355	4.56	348.5