

Heat shrinkable straight-through joint  
for unarmoured polymeric cables

Universal applications to connect low voltage 4-core plastic insulated cables or conductors insulated with PVC, PE and XLPE. Suitable for compression connectors on aluminium or copper cables.



Product description

Article name	SMH4D 95-150
Article number	145471
Optional accessory	Compression connectors (see Connecting technology)

Characteristics
Compact dimensions
Wide conductor and cross-section range
Resistant to chemical agents
Resistant to alkaline earth elements
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
Transversely waterproof
High electrical insulating values
High mechanical strength

Applications
Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork

## Technical data



Article name	SMH4D 95-150
Article number	145471
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	DIN VDE 0278-1
	DIN VDE 0278-3
Length L1	760 mm
Nominal cross section Polymeric cable unarmoured per conductor 4x min	95 mm <sup>2</sup>
Nominal cross section Polymeric cable unarmoured per conductor 4x max	150 mm <sup>2</sup>

## Logistics data

Article name	SMH4D 95-150
Article number	145471
Delivery scope	Inner sleeves
	Outer sleeve
	Cleaning tissue
	Emery cloth
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39173900
EAN/GTIN	4010311004211

## Packaging data

Packaging type	Bag1	Pal. EU
Content quantity	1	100
Unit of measure	Piece	Piece
Lenght (mm)	820	1200
Width (mm)	130	800
Height (mm)	105	770
Net weight (kg)	0.604	60.4
Gross weight (kg)	0.604	89.4