

Heat shrinkable straight-through joint
for flexible cables

Universally suitable for connecting conductors insulated with EPR (e.g. A07RN-F, H07RN-F). Suitable for compression connectors.



Product description

Article name	SMH5G 70-120
Article number	205102

Characteristics
Compact dimensions
Wide conductor and cross-section range
Resistant to chemical agents
Resistant to alkaline earth elements
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
Transversely waterproof
High electrical insulating values
High mechanical strength

Applications
Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork

Technical data

Article name	SMH5G 70-120
Article number	205102
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L1	700 mm
Nominal cross section Polymeric conductor unarmoured per conductor 4x min	70 mm ²
Nominal cross section Polymeric conductor unarmoured per conductor 4x max	120 mm ²

Logistics data

Article name	SMH5G 70-120
Article number	205102
Delivery scope	Outer sleeve
	Inner sleeves
	Filling material
	Cleaning tissue
	Emery cloth
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39173900
EAN/GTIN	4010311118789

Packaging data

Alternative unit of measure	Bag1
Base quantity	1
Base unit of measure	Piece
Lenght (mm)	729
Width (mm)	190
Height (mm)	140
Net weight (kg)	1.018
Gross weight (kg)	1.018