

Heat shrinkable straight-through joint
for unarmoured polymeric cables

Universally suitable for connecting polymeric cables or conductors insulated with PVC, PE and XLPE (e.g. N(A)YY, NYM, TT). Suitable for compression connectors on aluminium or copper cables.



Product description

Article name	SMH4 25-95
Article number	145332
Optional accessory	Compression connectors (see Connecting technology)

Characteristics
Compact dimensions
Wide conductor and cross-section range
Resistant to chemical agents
Resistant to alkaline earth elements
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
Transversely waterproof
High electrical insulating values
High mechanical strength

Applications
Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork

[illegible]

Article name	SMH4 25-95
Article number	145332
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L1	600 mm
Nominal cross section Polymeric cable unarmoured per conductor 4x min	25 mm²
Nominal cross section Polymeric cable unarmoured per conductor 4x max	95 mm²

Logistics data

Article name	SMH4 25-95
Article number	145332
Delivery scope	Outer sleeve
	Inner sleeves
	Cleaning tissue
	Emery cloth
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39173900
EAN/GTIN	4010311000282

Packaging data

Alternative unit of measure	Bag1	Pal. OW
Base quantity	1	200
Base unit of measure	Piece	Piece
Lenght (mm)	637	1200
Width (mm)	153	800
Height (mm)	87	1130
Net weight (kg)	0.426	85.2
Gross weight (kg)	0.426	103.4