

Heat shrinkable straight-through joint
for unarmoured polymeric cables

Universally suitable for connecting polymeric cables or conductors insulated with PVC, PE and XLPE (e.g. N(A)YY, NYM, TT). Suitable for compression connectors on aluminium or copper cables.



Product description

Article name	SMH1 95-240
Article number	150160
Optional accessory	Compression connectors (see Connecting technology)

Characteristics
Compact dimensions
Wide conductor and cross-section range
Resistant to chemical agents
Resistant to alkaline earth elements
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
Transversely waterproof
High electrical insulating values
High mechanical strength

Applications
Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork

↓

Pos.	Designation	Dimensions	
L1	Length	200 mm	

Date / date:	Mar / mers:	Article / article:
17/01/2023	BD	Article no / Article no / ref base to scale
22/12/2023	BD	Article no / Article no / ref base to scale
22/12/2023	BD	Article no / Article no / ref base to scale

/// BBC

CELLPACK

Electrical Products

Designation / description:	Quantity / quantity:
SMH1 85-240	1
Article no / Article no	Article / article
CEP0003 150160	1

Article name	SMH1 95-240
Article number	150160
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L1	500 mm
Nominal cross section Polymeric cable unarmoured per conductor 1x min	95 mm²
Nominal cross section Polymeric cable unarmoured per conductor 1x max	240 mm²

Logistics data

Article name	SMH1 95-240
Article number	150160
Delivery scope	Outer sleeve
	Inner sleeves
	Cleaning tissue
	Emery cloth
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39173900
EAN/GTIN	4010311028583

Packaging data

Alternative unit of measure	Bag1	Pal. OW
Base quantity	1	250
Base unit of measure	Piece	Piece
Lenght (mm)	543	1200
Width (mm)	201	800
Height (mm)	47	1130
Net weight (kg)	0.265	66.25
Gross weight (kg)	0.265	84.45