

Heat shrinkable straight-through joint  
for tape and wire armoured polymeric cables

Universally suitable for connecting armoured polymeric cables insulated with PVC, PE and XLPE (e.g. N(A)YY, NYM, TT). Suitable for compression connectors on aluminium and copper conductors.



Product description


Article name	SMHA4 35-150
Article number	130945
Optional accessory	Compression connectors (see Connecting technology)

Characteristics
Compact dimensions
Wide conductor and cross-section range
Resistant to chemical agents
Resistant to alkaline earth elements
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
Transversely waterproof
High electrical insulating values
High mechanical strength

Applications
Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork



Technical data



Article name	SMHA4 35-150
Article number	130945
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L1	850 mm
Nominal cross section Polymeric cable armoured per conductor 4x min	35 mm²
Nominal cross section Polymeric cable armoured per conductor 4x max	150 mm²



## Logistics data

Article name	SMHA4 35-150
Article number	130945
Delivery scope	Outer sleeve
	Inner sleeves
	Armour crossover kit
	Cleaning tissue
	Emery cloth
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39173900
EAN/GTIN	4010311086064

## Packaging data

Alternative unit of measure	Bag1	Pal. EU
Base quantity	1	75
Base unit of measure	Piece	Piece
Lenght (mm)	950	1200
Width (mm)	135	800
Height (mm)	105	1130
Net weight (kg)	1.041	78.075
Gross weight (kg)	1.041	107.075