

Heat shrinkable straight-through joint

for tape and wire armoured polymeric cables

Universally suitable for connecting armoured polymeric cables insulated with PVC, PE and XLPE (e.g. N(A)YY, NYM, TT). Suitable for compression connectors on aluminium and copper conductors.



Product description

Article name	SMHA4 16-50
Article number	145243
Optional accessory	Compression connectors (see Connecting technology)

Characteristics
Compact dimensions
Wide conductor and cross-section range
Resistant to chemical agents
Resistant to alkaline earth elements
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
Transversely waterproof
High electrical insulating values
High mechanical strength

Applications
Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork

Article name	SMHA4 16-50
Article number	145243
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L1	650 mm
Nominal cross section Polymeric cable armoured per conductor 4x min	16 mm²
Nominal cross section Polymeric cable armoured per conductor 4x max	50 mm²

Logistics data

Article name	SMHA4 16-50
Article number	145243
Delivery scope	Outer sleeve
	Inner sleeves
	Armour crossover kit
	Cleaning tissue
	Emery cloth
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39173900
EAN/GTIN	4010311095448

Packaging data

Alternative unit of measure	Bag1	Pal. OW
Base quantity	1	100
Base unit of measure	Piece	Piece
Length (mm)	700	1200
Width (mm)	80	800
Height (mm)	57	1130
Net weight (kg)	0.512	51.2
Gross weight (kg)	0.512	69.4