

Heat shrinkable straight-through joint

for polymeric cables with concentric conductor

Universally suitable for connecting polymeric-insulated cables and conductors with concentric conductors and insulations made of PVC, PE and XLPE (e.g. N(A)YCY, N(A)YC(W)Y, GKN). Suitable for compression connectors.



Product description

Article name	SMHC1 95-240
Article number	152521
Optional accessory	Compression connectors (see Connecting technology)

Characteristics	Applications
Compact dimensions	Indoor
Wide conductor and cross-section range	Outdoor
Resistant to chemical agents	Underground
Resistant to alkaline earth elements	Water
Stabilized against UV rays	Installation ducts
Free from paint-wetting inhibiting substances	Ductwork
Halogen-free	
Transversely waterproof	
High electrical insulating values	
High mechanical strength	

Technical data



Article name	SMHC1 95-240
Article number	152521
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L1	500 mm
Nominal cross section Polymeric cable with concentric conductor per conductor 1x min	95 mm ²
Nominal cross section Polymeric cable with concentric conductor per conductor 1x max	240 mm ²

Logistics data

Article name	SMHC1 95-240
Article number	152521
Delivery scope	Outer sleeve
	Inner sleeves
	Copper braid tape
	Cleaning tissue
	Emery cloth
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39173900
EAN/GTIN	4010311029016

Packaging data

Packaging type	Bag1
Content quantity	1
Unit of measure	Piece
Length (mm)	627
Width (mm)	199
Height (mm)	77
Net weight (kg)	0.443
Gross weight (kg)	0.443