

## Heat shrinkable straight-through joint

with screw connectors for unarmoured polymeric cables and conductors

Universally suitable for connecting polymeric cables or conductors insulated with PVC, PE and XLPE (e.g. N(A)YY, NYM, TT). With mechanical connectors with shear head bolts, suitable for aluminium or copper cables.



### Product description

Article name	SMHSV5 16-95
Article number	357687


#### Characteristics

Compact dimensions
Wide conductor and cross-section range
Resistant to chemical agents
Resistant to alkaline earth elements
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Halogen-free
Transversely waterproof
High electrical insulating values
High mechanical strength

#### Applications

Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork

## Technical data



Article name	SMHSV5 16-95
Article number	357687
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L1	900 mm
Nominal cross section Polymeric cable unarmoured per conductor 5x min	16 mm <sup>2</sup>
Nominal cross section Polymeric cable unarmoured per conductor 5x max	95 mm <sup>2</sup>

## Logistics data

Article name	SMHSV5 16-95
Article number	357687
Delivery scope	Outer sleeve
	Inner sleeves
	Screw connectors with shear head bolts
	Cleaning tissue
	Emery cloth
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39173900
EAN/GTIN	4010311172620

## Packaging data

Packaging type	Bag1
Content quantity	1
Unit of measure	Piece
Length (mm)	921
Width (mm)	201
Height (mm)	97
Net weight (kg)	0.979
Gross weight (kg)	0.979