

Heat shrinkable straight-through joint

with crimp connectors for control cables and signal cables

Universally suitable for connecting polymeric cables or conductors insulated with PVC, PE and XLPE (e.g. N(A)YY, NYM, TT). Suitable for compression connectors on aluminium or copper cables.



Product description

Article name	SMH 12/14 1.5-2.5
Article number	145489

Characteristics	Applications
Compact dimensions	Indoor
Resistant to chemical agents	Outdoor
Resistant to alkaline earth elements	Underground
Stabilized against UV rays	Water
Free from paint-wetting inhibiting substances	Installation ducts
Transversely waterproof	Ductwork
High electrical insulating values	
High mechanical strength	

Technical data



Article name	SMH 12/14 1.5-2.5
Article number	145489
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L1	500 mm
Control and signal cable Number of conductors min	12 Pieces
Control and signal cable Number of conductors max	14 Pieces
Nominal cross section Control and signal cable per conductor min	1.5 mm ²
Nominal cross section Control and signal cable per conductor max	2.5 mm ²

Logistics data

Article name	SMH 12/14 1.5-2.5
Article number	145489
Delivery scope	Outer sleeve
	Inner sleeves
	Heat shrinkable crimp connectors
	Cleaning tissue
	Emery cloth
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39173900
EAN/GTIN	4010311005348

Packaging data

Alternative unit of measure	Bag1	Case
Base quantity	1	10
Base unit of measure	Piece	Piece
Length (mm)	510	630
Width (mm)	80	175
Height (mm)	50	175
Net weight (kg)	0.126	1.26
Gross weight (kg)	0.126	1.56