

One-component gel based on silicon
ready-to-use with nozzle

Standard cartridge, filled with extremely sticky one-component sealing compound suitable for electrical insulation and protection against corrosion, also recommended for temporal solutions.



Product description

Article name	SOFT GEL 310
Article number	364723

Characteristics
Ready-to-use
Very sticky, does not drip
Re-accessible
Non-labelled and non-toxic
Reusable
Halogen-free
UV rays stable

Applications
Indoor
Outdoor
Plug-in protection
Protection against corrosion and insects
For electrical systems up to 1 kV

Technical data

Article name	SOFT GEL 310
Article number	364723
Content	310 ml
Viscosity (23 °C)	40000 mPas
Density	0.97 g/cm ³
Working temperature min	0 °C
Working temperature max	40 °C
Heat resistance min	-40 °C
Heat resistance max	150 °C
Specific volume resistivity	$\geq 2 \times 10^{14} \Omega \text{ cm}$
Specific volume resistivity (associated standard)	HD 429
Dielectric strength	$\geq 10 \text{ kV/mm}$
Dielectric strength (associated standard)	IEC 60243-1

Logistics data

Article name	SOFT GEL 310
Article number	364723
Delivery scope	SOFT GEL in a cartridge with nozzle
Shelf life description	Unlimited shelf life
	The cartridge can be stored open
Storage temperatur max	40 °C
Storage temperatur min	0 °C
Country of origin	Germany
Customs tariff number	39100000
EAN/GTIN	4010311176970

Packaging data

Alternative unit of measure	Bag1	Carton	Pal. EU
Base quantity	1	12	1344
Base unit of measure	Piece	Piece	Piece
Lenght (mm)	231	231	1198
Width (mm)	64	158	790
Height (mm)	47	261	1040
Net weight (kg)	0.35	4.2	470.4
Gross weight (kg)	0.35	4.5	499.4