

Heat shrinkable thin wall tube  
halogen-free shrink ratio 2 : 1 without adhesive

The heat shrinkable tubes type SRC1 are thin-walled, without adhesive with a shrinkage ratio of 2:1. Typical applications are the protection of cables against chemical influences as well as good mechanical protection.



Product description

|                |   |
|----------------|---|
| Article name   | SRC1 25.4-12.7  |
| Article number | 145129  |
| Notes          | A standard spool may include sections which have been tied together.<br>Other lengths available on request. |

|   |
|---|
| Characteristics                               |
| Thin wall                                     |
| Without adhesive                              |
| Inscribable                                   |
| Resistant to chemical agents                  |
| Stabilized against UV rays                    |
| Non-corrosive                                 |
| Free from paint-wetting inhibiting substances |
| Halogen-free                                  |
| Infusible                                     |
| High tensile strength                         |
| Superior electrical properties                |
| High tensile strength                         |
| Resistant to cold flow (thermally stable)     |
| High flexibility                              |

|                       |
|-----------------------|
| Applications          |
| Insulating            |
| Bundling              |
| Marking               |
| Corrosion protection  |
| Mechanical protection |

## Technical data

|   |                          |
|---|--------------------------|
| Article name  | SRC1 25.4-12.7           |
| Article number  | 145129                   |
| Test standards  | MIL-I-23053/5 Class 1    |
|   | MIL-I-23053/5 Class 2    |
| Materials   | Cross-linked polyolefin  |
|   | Free of lead and cadmium |
| Selection Note  | lengths                  |
| Length L  | 1 m                      |
| Colours   | black                    |
| Inner diameter before shrinking (inch)                | 1"                       |
| Inner diameter before shrinking (mm)                  | 25.4 mm                  |
| Inner diameter after shrinking (mm)                   | 12.7 mm                  |
| Recovered wall thickness                              | 0.89 mm                  |
| Elongation at break                                   | 200 %                    |
| Elongation at break (associated standard)             | ASTM D 638               |
| Tensile strength at break                             | 10 MPa                   |
| Tensile strength at break (associated standard)       | ASTM D 638               |
| Longitudinal shrinkage                                | +/- 10 %                 |
| Longitudinal shrinkage (associated standard)          | ASTM D 2671              |
| Shrink ratio  | 2 : 1                    |
| Shrinkage temperature                                 | > 90 °C                  |
| Flexibility at low temperatures                       | -30 °C                   |
| Flexibility at low temperatures (associated standard) | ASTM D 2671              |
| Operation temperature min                             | -30 °C                   |
| Operation temperature max                             | 105 °C                   |
| Operation temperature (associated standard)           | IEC 216                  |
| Specific volume resistivity                           | 10 <sup>14</sup> Ω cm    |
| Specific volume resistivity (associated standard)     | ASTM D 257               |
| Corrosion   | none                     |
| Corrosion (associated standard)                       | ASTM D 2671              |
| Resistance to fungus and decay                        | No growth                |
| Resistance to fungus and decay (associated standard)  | AMS-DTL-7444             |

## Logistics data

|                        |   |
|------------------------|---|
| Article name           | SRC1 25.4-12.7                            |
| Article number         | 145129                                    |
| Delivery scope         | Thin wall heat shrinkable tube in lengths |
| Shelf life description | Unlimited shelf life                      |
| Country of origin      | Poland                                    |
| Customs tariff number  | 39173200                                  |
| EAN/GTIN               | 4010311035352                             |

## Packaging data

|                             |       |        |
|-----------------------------|-------|--------|
| Alternative unit of measure | Bag   | Carton |
| Base quantity               | 10    | 70     |
| Base unit of measure        | Piece | Piece  |
| Lenght (mm)                 | 1020  | 480    |
| Width (mm)                  | 50    | 405    |
| Height (mm)                 | 60    | 225    |
| Net weight (kg)             | 0.43  | 3.01   |
| Gross weight (kg)           | 0.435 | 3.31   |