

Heat shrinkable medium wall tube  
flexible shrink ratio 3 : 1 or 4 : 1 with adhesive

The heat shrinkable tubes type SRUM are medium-walled, with thermoplastic adhesive with a shrinkage ratio of 3:1 or 4:1. Typical applications are the protection of cables against moisture and pressure for cables as well as suitable for heat shrinkable joints and terminations.



Product description

Article name	SRUM 12-4
Article number	127474
Notes	A standard spool may include sections which have been tied together. Other lengths available on request.

Characteristics
Medium wall
With hot melt adhesive
Inscribable
Resistant to chemical agents
Stabilized against UV rays
Free from paint-wetting inhibiting substances
Non-corrosive
Infusible
High flexibility
Superior electrical properties
High tensile strength
Resistant to cold flow (thermally stable)
Self-extinguishing

Applications
Insulating
Bundling
Marking
Corrosion protection
Mechanical protection

## Technical data

Article name	SRUM 12-4
Article number	127474
Test standards	MIL-I-23053/4
Materials	Cross-linked polyolefin
	Free of lead and cadmium
Selection Note	spools
Length L	100 m
Colours	black
Inner diameter before shrinking (mm)	12 mm
Inner diameter after shrinking (mm)	4 mm
Recovered wall thickness	2.3 mm
Elongation at break	300 %
Elongation at break (associated standard)	ASTM D 638
Tensile strength at break	11 MPa
Tensile strength at break (associated standard)	ASTM D 638
Longitudinal shrinkage	+/- 15 %
Longitudinal shrinkage (associated standard)	ASTM D 2671
Operating temperature range min	-55 °C
Operating temperature range max	110 °C
Operating temperature range (associated standard)	IEC 216
Shrinkage temperature	> 110 °C
Burning behaviour	self-extinguishing
Burning behaviour (associated standard)	UL 224
Flexibility at low temperatures	-55 °C
Flexibility at low temperatures (associated standard)	ASTM D 2671
Specific volume resistivity	10 <sup>14</sup> Ω cm
Specific volume resistivity (associated standard)	ASTM D 257
Dielectric strength	15 kV/mm
Dielectric strength (associated standard)	ASTM D 2671
Corrosion	none
Corrosion (associated standard)	ASTM D 2671
Resistance to fungus and decay	No growth
Resistance to fungus and decay (associated standard)	AMS-DTL-7444

## Logistics data

Article name	SRUM 12-4
Article number	127474
Delivery scope	Medium wall heat shrinkable tube on spool
Shelf life description	Unlimited shelf life
Country of origin	Poland
Customs tariff number	39173200
EAN/GTIN	4010311009384

## Packaging data

Alternative unit of measure	Coil	Carton
Base quantity	100	300
Base unit of measure	Meter	Meter
Length (mm)	392	395
Width (mm)	392	395
Height (mm)	115	395
Net weight (kg)	3.2	9.6
Gross weight (kg)	3.212	9.9