

Trifurcation kit for CHE, CHESK and CTS, CTKS for 3-core polymeric cables up to 36 kV

The trifurcation kit allows the installation of products designed for 1-core-cable on 3-core-cable, suitable for different cable types.



Product description

Article name	AS-1/CTS/CTKS
Article number	354194

Characteristics

- Quick, safe and easy assembly
- Superior electrical properties
- High mechanical strength

Applications

- Indoor/Outdoor
- Protection against dust and moisture

Technical data

Article name	AS-1/CTS/CTKS
Article number	354194
Voltage levels	U0/U (Um) 6/10 (12) kV - 19/33 (36) kV
Applicable for	CTS, CTKS 630 A 12 kV
Nominal cross section 12 kV min	95 mm ²
Nominal cross section 12 kV max	150 mm ²
Diameter over core insulation after removal of the outer conductive layer min	14.7 mm
Applicable for	CTS, CTKS 630 A 24 kV
Nominal cross section 12 kV min	50 mm ²
Nominal cross section 12 kV max	95 mm ²
Nominal cross section 24 kV min	25 mm ²
Nominal cross section 24 kV max	70 mm ²
Diameter over core insulation after removal of the outer conductive layer min	14.7 mm

Logistics data

Article name	AS-1/CTS/CTKS
Article number	354194
Delivery scope	Heat shrinkable tubes
	Spreader cap
	Mastic tape
	Copper braid tube
	Assembly material
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39173900
EAN/GTIN	4010311171357

Packaging data

Alternative unit of measure	Bag1	Pal. OW
Base quantity	1	10
Base unit of measure	Piece	Piece
Lenght (mm)	1106	1200
Width (mm)	213	800
Height (mm)	97	1130
Net weight (kg)	0.678	6.78
Gross weight (kg)	0.678	24.98