

## Zestaw rozdzielający dla CHE, CHESK i CTS, CTKS

do kabli 3-żyłowych do 36 kV

Zestaw trifurkacyjny umożliwia instalację produktów przeznaczonych dla kabla 1-żyłowego na kablu 3-żyłowym, odpowiednich dla różnych typów kabli.



### Opis produktu

Oznaczenie artykułu	AS-2/CTS/CTKS
Numer przedmiotu	354196

#### Właściwości

Szybki, prosty i bezpieczny montaż  
Bardzo dobre właściwości elektryczne  
Wysoka wytrzymałość mechaniczna

#### Zastosowanie

Wnętrze/Napowietrzny  
Ochrona przed pyłem i wilgocią

## Dane techniczne

Oznaczenie artykułu	AS-2/CTS/CTKS
Numer przedmiotu	354196
Poziomy napięcie	U0/U (Um) 6/10 (12) kV - 19/33 (36) kV
Applicable for	CTS, CTKS 630 A 24 kV
Nominal cross section 12 kV min	150 mm <sup>2</sup>
Nominal cross section 12 kV max	240 mm <sup>2</sup>
Nominal cross section 24 kV min	95 mm <sup>2</sup>
Nominal cross section 24 kV max	240 mm <sup>2</sup>
Diameter over core insulation after removal of the outer conductive layer min	22 mm
Applicable for	CTS, CTKS 630 A 24 kV
Nominal cross section 12 kV min	240 mm <sup>2</sup>
Nominal cross section 12 kV max	300 mm <sup>2</sup>
Nominal cross section 24 kV min	240 mm <sup>2</sup>
Nominal cross section 24 kV max	300 mm <sup>2</sup>
Diameter over core insulation after removal of the outer conductive layer min	23.7 mm
Applicable for	CTS, CTKS 630 A 36 kV
Nominal cross section 24 kV min	95 mm <sup>2</sup>
Nominal cross section 24 kV max	240 mm <sup>2</sup>
Nominal cross section 36 kV min	50 mm <sup>2</sup>
Nominal cross section 36 kV max	150 mm <sup>2</sup>
Diameter over core insulation after removal of the outer conductive layer min	22 mm
Applicable for	CTS, CTKS 630 A 36 kV
Nominal cross section 24 kV min	240 mm <sup>2</sup>
Nominal cross section 24 kV max	240 mm <sup>2</sup>
Nominal cross section 36 kV min	150 mm <sup>2</sup>
Nominal cross section 36 kV max	240 mm <sup>2</sup>
Diameter over core insulation after removal of the outer conductive layer min	30.8 mm

## Dane logistyczne

Oznaczenie artykułu	AS-2/CTS/CTKS
Numer przedmiotu	354196
Zakres dostawy	Rury termokurczliwe
	Palczatka
	Taśma mastykowa
	Rękaw miedziany pleciony
	Osprzęt montażowy
	Instrukcja montażowa
Okres przydatności - dodatkowy opis	Nieograniczony czas przechowywania
Numer taryfy celnej	39173900
EAN/GTIN	4010311171364

## Dane opakowania

Alternatywna jednostka opakowania	Torebka1
Ilość podstawowa	1
Podstawowa jednostka opakowania	Sztuka
Długość (mm)	1096
Szerokość (mm)	180
Wysokość (mm)	117
Waga netto (kg)	0.821
Waga brutto (kg)	0.821