

Protective insulating varnish

for protection against chemical exposure

One-component lacquer for electronics, high surface and volume resistances, good dielectric strength, low dielectric constant and loss factors, elastic, abrasion and adhesion resistant, durable and not solderable.



Product description

Article name	URETHAN Spray
Article number	124017

Characteristics
Highly resistant

Applications
Corrosion protection
Moisture protection
Protection of appliances and materials against chemical exposure
Protective coating for electric motors, transformers, components and appliances

Technical data

Article name	URETHAN Spray
Article number	124017
Content	0.4 l
Colours	transparent color
Drying time	30 minutes
Flash point	-97 °C
Density	0.79 g/cm ³
Dielectric strength	82.9 kV/mm

Logistics data

Article name	URETHAN Spray
Article number	124017
Delivery scope	Protective insulating varnish
Shelf life	24 Month
Storage temperatur max	25 °C
Storage temperatur min	20 °C
Country of origin	France
Customs tariff number	32100010
EAN/GTIN	4010311048963

Packaging data

Alternative unit of measure	Tin	Carton	Pal. EU
Base quantity	1	12	900
Base unit of measure	Piece	Piece	Piece
Lenght (mm)	64	270	1200
Width (mm)	64	202	800
Height (mm)	200	203	1400
Net weight (kg)	0.372	4.464	334.8
Gross weight (kg)	0.372	4.764	363.8