

Screw connector Al-Cu

for low voltage

Screw connector for aluminium and copper conductors with grub screws.



Product description

Article name	VS 4-50
Article number	126214

Applications

For connecting conductors RM/SM (class 2), RE/SE (class 1) according to DIN EN/IEC 60228 (VDE 0295)

Technical data

Article name	VS 4-50
Article number	126214
Materials	Galvanic tinned
Selection Note	VS = For heat shrinkable cable joints
Nominal cross section RM min	4 mm ²
Nominal cross section RM max	35 mm ²
Nominal cross section SM min	4 mm ²
Nominal cross section SM max	35 mm ²
Nominal cross section SE min	4 mm ²
Nominal cross section SE max	50 mm ²
Nominal cross section RE min	4 mm ²
Nominal cross section RE max	50 mm ²
Number of bolts	2 Pieces

Logistics data

Article name	VS 4-50
Article number	126214
Delivery scope	Screw connector
Country of origin	Poland
Customs tariff number	85369010
EAN/GTIN	4010311062419

Packaging data

Alternative unit of measure	Bag1	Carton
Base quantity	1	100
Base unit of measure	Piece	Piece
Lenght (mm)	37	195
Width (mm)	15	150
Height (mm)	15	70
Net weight (kg)	0.016	1.6
Gross weight (kg)	0.016	1.9