

## Screw connector Al-Cu

for low voltage

Screw connector for aluminium and copper conductors with grub screws.



### Product description

Article name	VS 50-150
Article number	166373

### Applications

For connecting conductors RM/SM (class 2), RE/SE (class 1) according to DIN EN/IEC 60228 (VDE 0295)

## Technical data

Article name	VS 50-150
Article number	166373
Materials	Galvanic tinned
Selection Note	VS = For heat shrinkable cable joints
Nominal cross section RM min	35 mm <sup>2</sup>
Nominal cross section RM max	150 mm <sup>2</sup>
Nominal cross section SM min	35 mm <sup>2</sup>
Nominal cross section SM max	120 mm <sup>2</sup>
Nominal cross section SE min	50 mm <sup>2</sup>
Nominal cross section SE max	150 mm <sup>2</sup>
Nominal cross section RE min	50 mm <sup>2</sup>
Nominal cross section RE max	95 mm <sup>2</sup>
Number of bolts	4 Pieces

Logistics data

Article name	VS 50-150
Article number	166373
Delivery scope	Screw connector
Country of origin	France
Customs tariff number	85369010
EAN/GTIN	4010311075037

Packaging data

Packaging type	Bag1	Carton
Content quantity	1	20
Unit of measure	Piece	Piece
Lenght (mm)	67	195
Width (mm)	27	150
Height (mm)	27	80
Net weight (kg)	0.116	2.32
Gross weight (kg)	0.116	2.62