

Anti-corrosion spray

for subsequent galvanizing

ZINK SPRAY 171 binds to steel and iron surfaces using an electrochemical process of forming a flexible protection film. This gives the parts an active cathodic protection against corrosion.



Product description

Article name	ZINC SPRAY 171
Article number	124030
Notes	ZINK SPRAY 171 is not approved according to the the food regulations and the construction material norms release 8/76 from the Institute for Construction Technology.

Characteristics
Smooth, fine porous film
With hydrocarbon propellant (flammable)
Can be varnished
Can be spot-welded
Dries quickly
Unmarked in compliance with ARB material regulations
No hazard rating in compliance with VBF
Weatherproof
Electrically conductive
Frost-resistant

Applications
Long-lasting corrosion protection
Repairing of damaged zinc layers
Repairing of galvanised surfaces
Cold galvanising
Oxidation protection
Rust prevention
Cold galvanising
Oxidation protection
Rust prevention

Technical data

Article name	ZINC SPRAY 171
Article number	124030
Content	0.4 l
Colours	grey
Degree of zinc purity	99 %
Density	0.95 g/cm ³

Logistics data

Article name	ZINC SPRAY 171
Article number	124030
Delivery scope	Anti-corrosion spray
Shelf life	24 Month
Storage temperatur max	25 °C
Storage temperatur min	20 °C
Country of origin	Germany
Customs tariff number	32081090
EAN/GTIN	4010311005744

Packaging data

Alternative unit of measure	Tin	Carton	Pal. OW
Base quantity	1	12	1008
Base unit of measure	Piece	Piece	Piece
Lenght (mm)	70	280	1200
Width (mm)	70	220	800
Height (mm)	197	210	1400
Net weight (kg)	0.458	5.496	461.664
Gross weight (kg)	0.458	5.796	479.864